

# Backpack Jammer



## Applications

- Anti-IED Jammer
- VIP and EOD Protection

## Features

- CDMA, PCS, WCDMA, GSM850/900, GSM1800, GSM1900, Wi-Fi(2.4GHz), Bluetooth, GPS
- Any 4 bands among above
- 20W output max. per band / total 80W output max.
- Battery operation (A/C option)

<b>Specification</b>	Model Number : GM-20MP / GM-50MP / GM-100MP
Frequency Band	CDMA, WCDMA, GSM850/900, GSM1800, GSM1900, PCS, Wi-Fi(2.4GHz), Bluetooth, GPS
Available Bands	Any 4 bands among 8 application bands
Output Power	4 bands : 20W max. / band (80W total) 2 bands : 100W max. / band (200W total)
Power Control	4 steps (5W / 10W / 15W / 20W) for power saving
Power Mute	On/Off Total bands / Each band
External Antenna	Attachable 2dBi omni-directional antenna
Display and Monitoring	RF Output Power per band, Voltage, Current
Protection Functions	Over Temperature Mismatch output power Auto power off in case of low DC power (under 22V)
Power Option	Battery Operation AC input Battery and AC input (Option)
Battery	Lithium Polymer / DC 48V
Battery Operation Time	1 hour in case of 80W maximum power (4 bands)
AC Power	AC 110 to 220V
Cooling	Fan cooling
Dimension	500(L) X 375(W) X 185(H) mm
Weight	23 Kg approx. (can be changed depending on options)

The specification subject to change without notice.



For the customized specification, price, and delivery ; Contact us

#1005, Woolim Lions Valley 3<sup>rd</sup>, 5445 Sangdaewon-dong, Jungwon-gu, Seoungnam-si, Gyeonggi-do 462-819, Korea  
TEL : +82-31-713-6105 FAX : +82-31-720-5011 [Http://www.genmixtech.com](http://www.genmixtech.com)

# Briefcase Jammer



## Applications

- Anti-IED Jammer
- VIP and EOD Protection

## Features

- CDMA, PCS, WCDMA, GSM850/900, GSM1800, GSM1900, Wi-Fi(2.4GHz), Bluetooth, GPS
- Any 4 bands among above
- 20W output max. per band / total 80W output max.
- Battery operation (A/C option)

<b>Specification</b>	Model Number : GM-05P / GM-10P / GM-20P
Frequency Band	CDMA, WCDMA, GSM850/900, GSM1800, GSM1900, PCS, Wi-Fi(2.4GHz), Bluetooth, GPS
Available Bands	Any 4 bands among 8 application bands 8 bands available (Option)
Output Power	4 bands : 3W max. / band (12W total) Option : higher power (5W / 10W / 20W per band)
Power Mute	On/Off Total bands / Each band
Antenna	2dBi omni-directional antenna (Internal or External)
Display and Monitoring	RF Output Power per band, Voltage, Current
Power Option	AC input Battery and AC input (Option)
Battery	Lithium Polymer / DC 28V
Battery Operation Time	1 hour in case of 12W maximum power (4 bands)
AC Power	AC 110 to 220V
Cooling	Fan cooling
Dimension	470(L) X 390(W) X 175(H) mm
Weight	13 Kg approx. (can be changed depending on options)

The specification subject to change without notice.



For the customized specification, price, and delivery ; Contact us

#1005, Woolim Lions Valley 3<sup>rd</sup>, 5445 Sangdaewon-dong, Jungwon-gu, Seoungnam-si, Gyeonggi-do 462-819, Korea  
TEL : +82-31-713-6105 FAX : +82-31-720-5011 [Http://www.genmixtech.com](http://www.genmixtech.com)