

Ku-Band 16W/20W/25W Block Up Converters



Applications

- High power BUCs for VSAT
- SatCom Applications

Features


- 42/43/44dBm min. Output Power
- Based on GaN Technology
- Very Low Power Consumption
- Small Size & Light Weight
- DC Input Range 36~70VDC (Optional)
- Internal Reference / M&C Function (Optional)

Model	GMU137145B01-16W	GMU137145B01-20W	GMU137145B01-25W
RF Frequency	14.0~14.5GHz 13.75~14.5GHz		
IF Frequency	950~1450MHz 950~1700MHz		
LO Frequency	13.05GHz 12.80GHz		
Output Power (min)	42dBm	43dBm	44dBm
Gain (min)	65dB		
Gain Variation over Frequency	2 dBp-p max. @ any 54 MHz 4 dBp-p max. @ over full bandwidth		
Gain Variation over Temperature	4 dBp-p max.		
IMD3	-26dBc max. @3dB total power back off from rated output power		
Spurious	In Band	-60 dBc	
	Out of Band	-50 dBc	
Input VSWR	2:1 max.		
Output Load VSWR	2 :1 max.		
Phase Noise	-63 dBc/Hz @ 100Hz		
	-73 dBc/Hz @ 1KHz		
	-83 dBc/Hz @ 10KHz		
	-93 dBc/Hz @ 100KHz		
	-103 dBc/Hz @ 1MHz		
DC Power	+36~+70VDC		
Power Consumption(max)	120W	150W	190W
M&C (Optional)	Monitor : Output power, Lock Status, Temperature		
	Control : Attenuator, Mute, LO selection		
	Interface : RS-232/RS-485		
Dimension (DC model)	233 x 140 x 88 mm		
Weight	3.5kg max.		
Temperature Range	Operation : -40 to +55°C		
	Storage : -40°C to +75°C		

The specification subject to change without notice.

Ku-Band 16W/20W/25W Block Up Converters

Mechanical Outline (GMU137145Bxx)



The specification subject to change without notice.